



RICOH
imagine. change.

**Cost
Effective
Colour
Printing**



**A3
SIZE**



RICOH SP C730DN

SPECIFICATIONS

GENERAL

Print speed:	32 ppm (A4) Colour and Monochrome
Warm-up time:	Less than 20 seconds
First Page out time:	Full colour: Less than 7 seconds* B/W: Less than 4 seconds*
Dimensions (WxDxH):	492x535x372 mm
Weight:	40 kg
Automatic Duplex:	Standard
Power source:	220 - 240 V, 50 - 60 Hz
Power consumption:	1300 W or less
Energy-saver mode:	Sleep 0.4W

CONTROLLER

Processor:	533MHz
Printer language:	Standard: PCL5c, PCL6, PostScript 3, PDF
Resolution:	600x600dpi, 1200x1200dpi
Memory:	512 MB Standard/ 1 GB Max
Hard Disk Drive:	160 GB Optional
Drivers:	PCL5c/PCL6: Windows® 2000/ XP/ Vista/Server 2003/ 2003R2/ Server 2008 PostScript 3: Windows® 2000/ XP/ Vista/ Server 2003/2003R2/ Server 2008, Macintosh 8.6 – 9.2.x (OS X Classic), Macintosh X Native (v.10.2 or later), UNIX (Mac OS X 10.1
Fonts:	PCL: 45 fonts + 13 fonts (International Fonts) PostScript 3:136 fonts

CONNECTIVITY

Network protocol:	TCP/IPX/SPX(Netware option)jou
Supported Environments:	Windows® 2000/ XP/ Vista Server 2003/2008 (32 bit, 64 bit) Novell® NetWare® 6.2 or later Macintosh 8.6 or later
Standard Interface:	Gigabit Ethernet (1000/100/10 Base-T), USB 2.0 (Type A & B), Option: Bi-directional IEEE 1284,

PAPER HANDLING

Paper input capacity:	Standard: 1 x 250-sheet paper tray 100-sheet bypass tray Optional 500 sheet paper feed unit (upto 3 Tray)
Paper output capacity:	Standard: 250 sheets*
Paper size:	Paper trays: A6- A3, legal, letter, envelope Bypass tray: A6 – A3, legal,letter, envelope
Paper weight:	Paper trays: 56-220 g/m ² Bypass tray: 56-256 g/m ² Duplex tray: 56-163 g/m ²
Media:	Plain paper, recycled paper, middle thick paper, thick paper, thin paper, transparencies, letterheads, labels, coated paper, water proof paper, pre-printed paper, envelopes

CONSUMABLES

Integrated Kit (Toner & Drum)	Black: 8,000 sheets C, M, Y: 7,000 sheets
Fusing Unit:	1,50,000 Pages/Unit

OTHER OPTIONS

Internal options:	Wireless LAN (IEEE 802.11a/b/g) HDD 160GB Bi-directional IEEE 1284 1 GB Memory optional
External options:	500-sheet paper tray (maximum 3)

The SP C730DN ships with an integrated starter Toner kit that yield 3,000 Black Prints and 2,500 Prints per Cyan, Magenta and Yellow. For availability of models, options and software, please consult your local Ricoh supplier.

- * Declared yield value in accordance with ISO/IEC 19798.
- * Paper Weight at 56g/m²
- * FPOT calculation paper pick up from input tray to paper out in output tray



ISO 9001: 2000 certified ISO 14001 certified Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure.

RICOH INDIA LIMITED, 2nd Floor, Salcon Aurum Building, Plot No.4, District Centre, Jasola, New Delhi-110 025. Tel: (011) 49103000, 49103100, 49103200
Ahmedabad, Bangalore, Chennai, Coimbatore, Cochin, Delhi, Hyderabad, Kolkata, Lucknow, Mumbai, Pune (ROM) & Goa, Ranchi
SMS: "RICOH" to 57272, Website: www.ricoh.co.in, Email: LP@ricoh.co.in

For More Information, please contact: